

Datasheet Conveyor Belt



NITTA CORPORATION OF HOLLAND

Berenkoog 25
1822 BH Alkmaar
The Netherlands

T: +31 (0)72 562 22 34
F: +31 (0)72 561 32 38

E: sales@nitta.nl
www.nittacorporation.com

- **NITTA BELT TYPE:**
2 LRAF 204
- **Nitta Japan code:**



Construction: 2 plies polyester, rigid, antistatic

	TOP COVER	INNER LAYER	BOTTOM SIDE	
Material:	PVC	PVC	Fabric	
Thickness:	0,4		-	mm (approx.)
Colour:	Green	Transparent	-	
Hardness:	80 Shore A		-	
Profile:	-		-	

Total thickness:	2	mm (approx.)
Weight:	2,3	kg/m² (approx.)
Max. width:	3000	mm
Belt support:	Sliderbed (Rollers), Flat	

Rating at 1% elongation:	8	N/mm
Advised pretension:	4 - 7	N/mm
Maximum allowable tension:	17	N/mm
Temperature range:	-10 to +80	°C

Minimum pulley diameters:		
Flexing:	25	mm
Backflexing:	50	mm

Special approval: Not applicable

Applications:

- General purpose conveying
- Conveying fruit and vegetables
- Conveying of boxes in packaging lines
- Conveying of tobacco and tea

Date of issue 03-04-2014-1

Your Partner In Belting Solutions

Data are valid at 15°C. Due to constant developments, Nitta reserves the right to make changes without prior notice. This issue succeeds all previous ones. Visit our website: www.nittacorporation.com