

# Datasheet Conveyor Belt



**NITTA CORPORATION  
OF HOLLAND**

Berenkoog 25  
1822 BH Alkmaar  
The Netherlands

T: +31 (0)72 562 22 34  
F: +31 (0)72 561 32 38

E: sales@nitta.nl  
www.nittacorporation.com

- **NITTA BELT TYPE:**  
**2 LRF 712/001**
- **Nitta Japan code:**



**Construction:** 2 plies polyester, rigid

	TOP COVER	INNER LAYER	BOTTOM SIDE	
<b>Material:</b>	PVC	PVC	Impregnated fabric	
<b>Thickness:</b>	1,2		-	<b>mm (approx.)</b>
<b>Colour:</b>	White	White	-	
<b>Hardness:</b>	65 Shore A		-	
<b>Profile:</b>	-		-	

<b>Total thickness:</b>	2,8		<b>mm (approx.)</b>
<b>Weight:</b>	3,4		<b>kg/m<sup>2</sup> (approx.)</b>
<b>Max. width:</b>	3000		<b>mm</b>
<b>Belt support:</b>	Sliderbed (Rollers), Flat		
<b>Rating at 1% elongation:</b>	8		<b>N/mm</b>
<b>Advised pretension:</b>	4 - 7		<b>N/mm</b>
<b>Maximum allowable tension:</b>	17		<b>N/mm</b>
<b>Temperature range:</b>	-10	<b>to</b>	+90 <b>°C</b>
<b>Minimum pulley diameters:</b>			
<b>Flexing:</b>	50		<b>mm</b>
<b>Backflexing:</b>	80		<b>mm</b>

**Special approval:** FDA, 10/2011/EC + amendments

**Applications:**  
 Conveying of meat, fish and poultry products  
 Conveyor belt for the food industry  
 In the dairy and bakery industry  
 Oil and grease resistant

Date of issue 11-12-2014-1

Your Partner In Belting Solutions

Data are valid at 15°C. Due to constant developments, Nitta reserves the right to make changes without prior notice. This issue succeeds all previous ones. Visit our website: www.nittacorporation.com